

TAMLITE LIGHTING 660 NW Peacock Blvd. Port St. Lucie, FL 34986 tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

DESCRIPTION

The TAFLL 12V floodlight is a versatile unit with multiple mounting options that satisfies many lighting applications. The TAFLL can be utilized as a landscape light as it can be adjusted to almost any position to direct light where needed.

HOUSING

Durable die cast powder coated aluminum housing with stainless hardware Finned heat sink designed to dissipate the radiant heat efficiently Specular aluminum back reflector creating a 160° beam spread

LENS

Fully gasketed tempered glass lens

LED₅

12V Ultra-bright 5000K, 30W LED producing over 2750 lumens LED light source does not attract most insects

MOUNTING

Mountable with yoke bracket

ACCESSORIES

18" power cord with waterproof male 12V plug included to allow versatility in many installation applications

LISTINGS/RATINGS/COMPLIANCE

Suitable for wet locations.

Fixtures are IP65 rated: protected from dust ingress and liquid projected from a 6.3mm nozzle against the enclosure from any direction.


WARRANTY

Guaranteed three years from the purchase date of the product, against mechanical defects in manufacturing.

NOTES

Product performance may vary depending on model and end user environment.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***



TAFLL Series













SPECIFICATIONS / DIMENSIONS

NOMINAL SIZE TAFLL **A** 8 7/8" **B** 7 1/4"

C 5 3/8"

B

ORDERING INFORMATION

Sample Part Code: TAFLL5030BZ-12

