

MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	



## SERIES SPECIFICATIONS

ESR-2

The ESR-2 series is a fixed optic thermoplastic emergency light that offers a low-profile design and uniform illumination in an easy to install fixture.



## LINE DRAWING



## CONSTRUCTION

### Housing

Injection molded, engineering grade, 5VA flame retardant high-impact resistant, thermoplastic

### Transfer switch

Internal solid-state transfer switch automatically connects the internal battery to lamp heads

### Lamp Heads

Two fixed optic 5.4W glare-free lamp heads with smooth thermoplastic reflector and plastic lens.

### Charger

Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

## ELECTRICAL SPECIFICATIONS

### Battery Type

6V Rechargeable Sealed Lead Acid

### Emergency Illumination

Minimum 90 Minutes

### Battery Recharge Time

24 Hours

### Low Voltage Disconnect

Prevents battery from deep discharge

### Frequency

60Hz

### Battery Discharge Time

1.5 Hours

MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

### ELECTRICAL SPECIFICATIONS (Cont.)

Operating Voltage  
120/277

Operating Temp  
20°C ~ 50°C

### AMPERAGE/WATTAGE

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
ESR-2	4.0	5.0	0.045	0.020

### MOUNTING SPECIFICATIONS

**Backplate**  
Snaps into place making internal electrical connections

**Surface Mount**  
"Easy Connect" backplate which fits most standard junction boxes.

Suitable for wall mount.

### CERTIFICATIONS/WARRANTY

**Listing**  
ETL Listed

**Compliance**  
Meets UL924, cULus, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

**Location Rating:**  
Suitable for damp locations

**Warranty**  
Guaranteed for five years from the purchase date of the product, against mechanical defects in manufacturing. Batteries are pro-rated for two years.



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

**ORDERING INFORMATION**

Part Number: ESR-2

ESR-2	
<b>SERIES</b>	<b>HOUSING COLOR</b>
ESR-2	[BLANK] : White
	[B] : Black

