



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

Catalog #:	04/03/2017
Project:	Type:
Prepared By:	

HOUSING

Two piece die cast aluminum driver housing and cast aluminum heat sink with white powder coat finish. Hanging eye hook, yoke mount bracket, safety cable, and cord with strain relief included. Integral pig tail connection for 0-10V dimming control.

MOUNTING

Mount with hanging eye hook or yoke mount bracket (included).

LIGHT OUTPUT PERFORMANCE

COLOR TEMP : 5000K

CRI: >82

DISTRIBUTION : Type V

LIFE : 50,000 Hrs.

	HBLED1505K	HBLED2105K
LUMENS:	17,371	25,045
LUMENS/WATT:	118.9	118.7

ELECTRICAL DETAILS

High performance CREE COB LED's and Meanwell dimmable driver
Max ambient temperature 40 degrees C

INPUT VOLTAGE : 120-277V

FREQUENCY: 50/60 Hz

	HBLED1505K	HBLED2105K
INPUT WATTAGE :	146.1	211
POWER FACTOR:	.91	.93

LISTINGS/RATINGS/COMPLIANCE

UL Listed
DLC listed (150W only)
IP65 rated

WARRANTY

Guaranteed for five years against mechanical defects in manufacturing.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

HBLED Series

COB LED High Bay



SPECIFICATIONS / DIMENSIONS

Width: 16" Height: 9"

ORDERING INFORMATION

Sample Part Code: HBLED1505K

HBLED	150	5K
SERIES	LAMP WATTAGE	COLOR TEMP

HBLED

[150]: 150 Watt
[210]: 210 Watt

[5K]: 5000K