

MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	


SERIES SPECIFICATIONS

LCLED SERIES

The large LED canopy has a low profile design with an integral heat sink for efficient LED performance. It is an excellent choice for lighting hallways and entrances, or any other application where a ceiling mount fixture is required.



LINE DRAWING



CONSTRUCTION

Housing

Die cast aluminum housing with integral heat sink. 1/2" threaded coin plugs for conduit entry on 2 sides.

Lens

Impact resistant poly-carbonate prismatic diffuser

Finish

Durable bronze powder coat finish.

ELECTRICAL SPECIFICATIONS

Input Voltage
120-277VAC

Input Current
0.7379A

Input Power
87.8

Power Factor
>.9

THD
<15%

CRI
>74

MODEL :	TYPE
PROJECT :	
PREPARED BY :	DATE :

ELECTRICAL SPECIFICATIONS CONT.

Frequency
50/60Hz

Efficacy
125+ lm/W

Color Temp
5000K

Duv
0.00192

Lumens
11100+ Lumens

Distribution
Type V


Life Span
50000 Hrs.

Min. Starting Temp
-40°C

Mounting

Quick mount back plate for easy surface or box mount installation, or 3/4" pendant mount (down rod provided by others).

PERFORMANCE SPECIFICATIONS



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL Listed

DLC Listing
Fixtures are DLC listed and featured of the Qualified Products List (QPL).*

Location Rating:
Suitable for wet locations

Warranty
Guaranteed for five years from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Sample Part Number: LCLED805K

LCLED	80	5K
SERIES	WATTAGE	COLOR TEMP
LCLED	[80] : 80 Watts	[5K] : 5000K

NOTES

*Not all product variations meet Design Light Consortium Qualifications. Please verify that the product is listed on the DLC products list at www.design-lightconsortium.org/QPL.