



# TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986  
tel: (772) 878-4944 or on the web at [www.tamliteusa.com](http://www.tamliteusa.com)

## SPECIFICATION & FEATURES

Catalog #:	04/03/2017
Project:	Type:
Prepared By:	

### HOUSING

Die cast aluminum housing with a durable textured bronze powdercoat finish. Housing has a removeable rear panel for driver access.

### LENS

Clear tempered flat glass lens

### MOUNTING

Unit is available with an adjustable 2 piece trunnion mount for mounting on flat surfaces, or a 2-3/8" adjustable slipfitter for tenon mounting. Trunnion mount model comes with a 6' SJTW UL cord without plug. Slipfitter mount model comes with 6" wire leads.

### LIGHT OUTPUT PERFORMANCE

	RBFLED805K	RBFLED1005K
TOTAL LUMENS :	6500	7800
LUMENS PER WATT :	80	85

COLOR TEMP. : 5000K  
CRI : 80  
DISTRIBUTION : TYPE II CUTOFF  
LIFE : 50000 Hrs

### ELECTRICAL DETAILS

	RBFLED805K	RBFLED1005K
INPUT WATTAGE :	80W	100W

INPUT VOLTAGE : 120-277V  
FREQUENCY : 50/60 Hz  
POWER FACTOR : .95  
MIN START TEMP :-30 DEGREES C

### WARRANTY

Guaranteed for 5 years against mechanical defects in manufacturing.

### LISTINGS/RATINGS/COMPLIANCE

UL Listed wet locations

\*\*\* SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE\*\*\*

# RBFLED Series

## LED 80/100W COB Flood



### SPECIFICATIONS / DIMENSIONS

Width: 12 1/4" Height: 8 1/2" Length: 7 1/4"

### ORDERING INFORMATION

Sample Part Code: RBFLED805KT

RBFLED		5K	
SERIES	WATTAGE	COLOR TEMP	MOUNTING
RBFLED	[80] : 80W [100] : 100W	[5K] : 5000K	[T] : Trunnion [S] : Slipfitter