



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

Catalog #:	04/03/2017
Project:	Type:
Prepared By:	

HOUSING

Die cast aluminum housing with a durable textured bronze powdercoat finish. Housing has a removeable rear panel for driver access.

LENS

Clear tempered flat glass lens

MOUNTING

Unit is available with a wide yoke mount for mounting on flat surfaces, or a 1/2" adjustable knuckle for groundstake or box mounting. Yoke mount model comes with a 6' SJTW UL cord without plug. Knuckle mount model comes with 6" wire leads.

LIGHT OUTPUT PERFORMANCE

TOTAL LUMENS : 3700
LUMENS PER WATT : 75
COLOR TEMP. : 5000K
CRI : 80
DISTRIBUTION : TYPE II CUTOFF
LIFE : 50000 Hrs

ELECTRICAL DETAILS

INPUT WATTAGE : 49.9W
INPUT VOLTAGE : 120-277V
FREQUENCY : 50/60 Hz
POWER FACTOR : .90
MIN START TEMP : -30 DEGREES C

WARRANTY

Guaranteed for 5 years against mechanical defects in manufacturing.

RBFLED Series

LED 50W COB Flood



SPECIFICATIONS / DIMENSIONS

Width: 5 1/2" Height: 7" Length: 10"

LISTINGS/RATINGS/COMPLIANCE

UL Listed wet locations

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

ORDERING INFORMATION

Sample Part Code: RBFLED505KK

RBFLED	50	5K	
SERIES	WATTAGE	COLOR TEMP	MOUNTING
RBFLED	[50] : 50W	[5K] : 5000K	[K] : 1/2" Knuckle [Y] : Yoke