



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

Catalog #:	08/21/2015
Project:	Type:
Prepared By:	

DESCRIPTION

The WL wraparound's clean and shallow fixture design makes it ideal for general illumination of areas such as hallways/corridors, commercial, education and office buildings.

HOUSING

- Code compliant steel housing
- Painted After Fabrication (PAF)- safe handling and added corrosion resistance

LENS

- Extruded low brightness prismatic acrylic lens

ELECTRICAL DETAILS

- NEC required ballast disconnect pre-installed

LISTINGS/RATINGS/COMPLIANCE

Fixtures are UL listed and suitable for damp locations.

WARRANTY

Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

NOTES

Product performance may vary depending on model and end user environment.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

WL Series

8' Tandem Fluorescent Wraparound



SPECIFICATIONS / DIMENSIONS



DIMENSIONS

	L	W	H
8'	96 1/4 "	11 1/4 "	3 3/8 "

ORDERING INFORMATION

Sample Part Code: WL4832DPS

WL	4	8		D	
SERIES	LAMP QTY	LENGTH	LAMP WATTAGE	VOLTAGE	BALLAST OPTION
WL	[4] : 4 Lamp	[8] : 8ft	[28] : 28W T5 [32] : 32W T8 [54] : 54W T5HO	[D] : 120-277V	[K] : 120-277V (2 ballast) [PS] : 120-277V Program Rapid Start [-DIM] : 120-277V 0-10V Series Elec. Dimming [-LPF] : 0.77 Low Ballast Factor 120-277V [-HPPF] : 1.18 High Ballast Factor 120-277V [B1] : Emerg. 500 Lum. 1 Lamp [B2] : Emerg. 1400 Lum. 1 Lamp [B3] : Emerg. 1400 Lum. 2 Lamp