

MODEL :	TYPE
PROJECT :	
PREPARED BY :	DATE :

SERIES SPECIFICATIONS

WL5LED4 SERIES

The WL5LED Wrap-Around fixture is a cost effective, energy-efficient utility lighting fixture for surface-mount application such as corridors, stairwells, public rooms, schools, hospitals, utility areas etc.



DIMENSIONS

Width: 6.10" Height: 2.69" Length: 46.65"

CONSTRUCTION

Housing Material

Heavy gauge steel

Color

White

Lens Material

Acrylic

Lens Type

Frosted

ELECTRICAL SPECIFICATIONS

Wattage

40W

Lumens

4800 Lm

Efficacy

122 Lm/W

CRI

> 82

CCT

4000-5000K

Ambient Temp.

-30°C ~ 45°C

Input Voltage

120-277 VAC

Frequency

50/60Hz

Power Factor

> 0.95

Lumen Maintenance

LM80/50,000 Hrs.

Dimming

0-10V

MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing:

UL Listed

Location Rating:

Suitable for damp locations

Warranty

Guaranteed for five years from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Sample Part Number: WL5LED4-48D1L850

WL5LED	4	-48	D1	L	8	
SERIES	LENGTH	LUMENS	DRIVER QTY.	TECHNOLOGY	CRI	COLOR TEMP
WL5LED	[4] : 4 Ft.	[-48] : 4800 Lumens	[D1] : 1 Driver	[L] : LED	[8] : 80 CRI	[40] : 4000K
						[50] : 5000K