



# TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986  
tel: (772) 878-4944 or on the web at [www.tamliteusa.com](http://www.tamliteusa.com)

## SPECIFICATION & FEATURES

Catalog #:	08/21/2015
Project:	Type:
Prepared By:	

### DESCRIPTION

The narrow wraparound's compact and shallow design makes it ideal for general illumination of small areas such as hallways/corridors, stairwells, education and office areas.

### HOUSING

- Code compliant steel housing
- Painted After Fabrication (PAF)- safe handling and added corrosion resistance
- Compact and shallow design- ideal for use in small areas or hallways/corridors

### LENS

- Extruded low brightness prismatic acrylic lens

### ELECTRICAL DETAILS

- NEC required ballast disconnect pre-installed

### LISTINGS/RATINGS/COMPLIANCE

Fixtures are UL listed and suitable for damp locations.

### WARRANTY

Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

### NOTES

Product performance may vary depending on model and end user environment.

\*\*\* SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE\*\*\*

# WLN Series

## Fluorescent Wraparound Narrow



### SPECIFICATIONS / DIMENSIONS



#### DIMENSIONS

	L	W	H
2'	24"	5 5/8"	4 5/8"
4'	48"	5 5/8"	4 5/8"
8'	96"	5 5/8"	4 5/8"

### ORDERING INFORMATION

Sample Part Code: WL1432D

WLN	1			D	
SERIES	LAMP QTY	LENGTH	LAMP WATTAGE	VOLTAGE	BALLAST OPTION
WLN	[1]: 1 Lamp	[2]: 2ft [4]: 4ft [8]: 8ft	[14]: 14W T5 [17]: 17W T8 [28]: 28W T5 [32]: 32W T8 [54]: 54W T5	[D]: 120-277V	[BLANK]: No Options [K]: 120-277V (2 ballast)* [PS]: 120-277V Program Rapid Start [-DIM]: 120-277V 0-10V Series Elec. Dimming [-LPF]: 0.77 Low Ballast Factor 120-277V [-HPF]: 1.18 High Ballast Factor 120-277V [B1]: Emerg. 500 Lum. 1 Lamp [B2]: Emerg. 1400 Lum. 1 Lamp* [B3]: Emerg. 1400 Lum. 2 Lamp* *Consult factory for 2ft fixture availability