



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

DESCRIPTION



TRRRT RGBW 24v

The TRRRT16KIT includes everything needed to bring RGBW color options to any job or installation. The RGBW, color changing, ribbon tape will allow you to create an ever changing ambiance to suit any mood desired. This kit includes an RF remote and receiver that makes changing colors, setting levels, and creating color shifts easy and fun. The 16' spool can be cut & spliced every 4 inches on clearly marked cut points to create custom lengths for your installation needs. Splice connectors included will allow you to add angles and jump gaps.



FEATURES AND WARRANTY

Intended Use

Residential, commercial, under cabinets, show cases, cove lighting.

Location Rating

Indoor use

Max Run Length

32ft

Dimmable

Dimmable with controller

Cuttable Length

Every 4"

Warranty

1-year limited warranty

ORDERING INFORMATION

EXAMPLE: TRRRT16KIT-RGBNW-WET

SERIES	COLOR KITS	COLOR TEMP	LOCATION
TRRRT16KIT	[-RGB]: COLOR CHANGE	[WW]: 3000K [NW]: 4000K	[-WET]: WET IP65

DIMENSIONS

SERIES	L	W	H
TRRRT16KIT-RGBWW-WET	16'	0.5"	0.125"
TRRRT16R-RGBWW-WET	16'	0.5"	0.125"
TRRRT16KIT-RGBNW-WET	16'	0.5"	0.125"
TRRRT16R-RGBNW-WET	16'	0.5"	0.125"

APPLICATION AND PERFORMANCE SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

LIGHTING SPECIFICATIONS

SERIES	WHITE LUMENS	LPW	WATTAGE	VOLTAGE	CRI
TRRR16KIT-RGBWW-WET	67	27.91	2.4W/FT	24V	90
TRRR16R-RGBWW-WET	67	27.91	2.4W/FT	24V	90
TRRR16KIT-RGBNW-WET	67	27.91	2.4W/FT	24V	90
TRRR16R-RGBNW-WET	67	27.91	2.4W/FT	24V	90

PERFORMANCE SPECIFICATIONS

TRRR70WDRIVER IN KIT

ELECTRICAL SPECIFICATIONS	
Nominal W	72W
Input	
Input Voltage (VAC)	120V-240V (+/- 10%)
Frequency Range (Hz)	50-60 Hz (+/- 5%)
Power Factor @ Full Load	>0.9
Output	
Output Voltage (VDC)	24v

ACCESSORIES

TRRR KITS include the following items:*

- 1x TRRR70DRIVER
- 2x TRRR2SC**
- 1x TRRR8FTSC**
- 1x TRRR-RF

*See Accessories sheet below for details and additional accessory information.

**TRRR- WET KITS include -WET IP65 connectors.



TRRR2SC (Included)

0549-5760

2" SPLICE CONN CBL 5 PIN

Voltage rating
12~36V



TRRR6SC

0549-5763

6" SPLICE CONN CBL 5 PIN

Voltage rating
12~36V



TRRR12SC

0549-5769

12" SPLICE CONN CBL 5 PIN

Voltage rating
12~36V



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

ACCESSORIES



TRRR24SC
0549-5772
24" SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



TRRR4FTSC
0549-5775
4FT SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



TRRR8FTSC (Included)
0549-5778
8FT SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



TRRRBSC-WET
0549-5826
BUTT SPLICE CONN 5 PIN
Voltage rating
12~36V



TRRR2WAY
0549-5784
2 WAY SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



TRRR70DWT
0549-5790
70W DIMMABLE DRIVER FOR TRRRT RG
Voltage rating
24V



TRRR70WDRIVER (Included)
0549-5787
70W 24V DRIVER FOR TRRRT RGBW SERIES
Voltage rating
24V



TRRR-BT
0549-5796
BLUE TOOTH RECEIVER/REMOTE FOR TRRRT SERIES
Voltage rating
12~36V



TRRR-RF (Included)
0549-5805
RF RECEIVER AND REMOTE FOR TRRRT SERIES
Voltage rating
12~36V



TRRRT-ALEXA CONTROL
0549-5799
ALEXA CONTROL FOR TRRRT SERIES
Voltage rating
12~36V

APPLICATION AND PERFORMANCE SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION