



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

Catalog #: Project:	01/06/2014
Project:	Type:
Prepared By:	

HOUSING

Die cast aluminum back housing with template for mounting over an electrical box, color matched polycarbonate front housing, coin plugs with O-rings for 1/2" conduit and photocell, bronze powdercoat finish.

REFLECTOR

Formed aluminum reflector

LENS

Clear ribbed polycarbonate lens

SOCKET

Plug-in type, 4 pin, GX24Q-4

MOUNTING

Cast-in template for mounting directly over a 4" recessed outlet box or use 1/2" surface mount conduit connection.

SOURCE/WATTAGE

Compact Fluorescent: 26W to 84W (1x26, 1x32, 1x42, 2x26, 2x32, 2x42)

ELECTRICAL DETAILS

BALLAST:

Electronic fluorescent ballasts are high power factor, Class P insulation, 120-277V, and have a starting temperature of 0° F (-18° C).

BATTERY BACKUP:

Provides up to 90 minutes of power for up to two lamps and has an operating temperature range of 32° to 122° F (0° to 50° C).

LISTINGS/RATINGS/COMPLIANCE

CSA or UL Listed
Suitable for wet locations.

WARRANTY

Guaranteed for one year against mechanical defects in manufacturing.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

VIV Series

Vivid Polycarbonate Wall Pack



SPECIFICATIONS / DIMENSIONS

Width: 11 3/4" Height: 11 3/4" Length: 7 1/4"

ORDERING INFORMATION

Sample Part Code: VIV242AEL

VIV		AE	L	
SERIES	LAMP WATTAGE	VOLTAGE	LAMPS INCLUDED	EMERGENCY BALLAST
VIV	[242] : 84W (2X42)	[AE] : 120-277	[L] : Lamp(s) Included	[Blank] : No Emergency Ballast [B1] : 120-277V Emergency Ballast