

CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: RLSRH-WP

DESCRIPTION





RLSRH-WP

Thermoplastic Wet Location LED Remote Heads









FEATURES AND SPECIFICATIONS

Construction

Weatherproof Thermoplastic

Housing Color

Bright White

Mounting

Universal mounting base plate included with mounting hardware.

Distance of maximum run is determined by system voltage, wire gaugeand total maximum wattage on the run. Suitable for wall or ceiling mount

Listings

UL Listed

Compliance

Meets UL 924, cULus, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

Location Rating

Suitable for wet locations


Warranty


Guaranteed for five years from the purchase date of the product, against mechanical defects in manufacturing.

LINE DRAWING
















CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: RLSRH-WP

ORDERING INFORMATION

EXAMPLE: RLSRH1-3.6WP

SERIES	# OF HEADS	VOLTAGE	HOUSING
RLSRH	[1]: 1 head	[-3.6]: 3.6 Volts	[WP] : Weatherproof Plastic
	[2]: 2 heads		

GENERAL INFORMATION

SERIES	# OF HEADS	VOLTAGE	TOTAL WATTAGE
RLSRH-WP	1 head	3.6 Volts	1.17 Watts
	2 heads		2.34 Watts

COMPATIBLE SERIES

LXP-RC	LXPC-RC	EXDC-RC	EXWTC-RC
ESLR-1RC	LSR-1RC	LXWTC-RC	-