



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: DL9068

SERIES SPECIFICATIONS



DL9068

6" Super Slope Non-IC New Work Housing

6" Super Slope Non-IC New Work housing for line voltage (120V) for use with 150W R40/PAR38 lamps. These are designed for use in non-insulated ceilings for general floor and task lighting.



CONSTRUCTION

Housing

- Non-IC housing, thermally protected against misuse of insulation materials and improper lamping.
- Housing designed to accommodate 7/12 to 12/12 pitch (30° to 45°) J-box is listed for through-branch circuit wiring
- (6) 1/2" knockouts, (1) 3/4" knockout and (4) pry-outs with Romex cable clamp
- 7 1/4" height allows use in 2" x 8" construction

Socket

- Medium base porcelain socket on adjustable mounting bracket for proper lamp positioning

Listings/Rating

- UL, C-UL listed for damp location and feed through wiring

Mounting

- Housing adjusts to accommodate various ceiling thicknesses
- Pre-installed hanger bars allow for free positioning within a 24" joist span
- Triangulated bar hangers with nails and leveling tab on the footprint
- Bar hangers are designed to fit T-bar spine without additional clamps for drop ceiling usage
- Ceiling Cuout Size : 6.65"x8.36"

Warranty

- Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFO

EXAMPLE: DL9068

SERIES	HOUSING
DL	9068

► Accessories

- TM48BL (150W Max) 6" Super Slope Baffle TM48RL
- (150W Max) 6" Super Slope Reflector

LINE DRAWING

