



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
 tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

Catalog #:	01/07/2016
Project:	Type:
Prepared By:	

IC Series

IC206ATQF

DESCRIPTION

6" Floating Socket IC Air-Tight New Work Housing
 Line Voltage 120V - 90W BR40, 75W R/PAR30, 60W A19

HOUSING

IC rated air-tight housing, thermally protected against misuse of insulation materials and improper lamping
 J-box is listed for through-branch circuit wiring with (6) 1/2" knockouts, (1) 3/4" knockout and (4) pry-outs Romex cable clamp
 Housing adjusts to accommodate various ceiling thicknesses
 Pre-installed hanger bars allow for free positioning within a 24" joist span
 Triangulated bar hangers with nails and leveling tab on the footprint
 Bar hangers are designed to fit T-bar spine without additional clamps for drop ceiling usage
 7 1/2" height allows use in 2" x 8" construction

SOCKET

Floating medium base porcelain socket for easy installation of full cone reflector style trims

LISTINGS/RATINGS/COMPLIANCE

UL, C-UL listed for damp location, feed through wiring and direct contact with insulation

Certified under ASTM-E283 for Airtight Construction

WARRANTY

Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

NOTES

Product performance may vary depending on model and end user environment.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***



SPECIFICATIONS / DIMENSIONS

ORDERING INFORMATION

Sample Part Code: IC206ATQF

IC			
SERIES	CONFIGURATION	OPTION	OPTION
IC	[206AT] : 6" IC Air-Tight New Work	[Q] : Quick Connect	[F] : Floating Socket