



24V DC LED RIBBON TAPE

Quantity with all the quality

High-quality accent lighting in the quantities contractors need. Traditional and dimmable 24V drivers and splice connectors ranging from 2" to 8' give greater option flexibility. Create intensity with Cool White or relax with Warm White color options. Need that extra punch? Available in high lumens in both color options.

- 75/108W 24V non-dimmable drivers
- 60/96W 24V dimmable drivers
- CRI of 95
- 100' ribbon reel (IP20 rated)
- 2" - 8' splice connectors available
- Standard & high lumen options



CSRT SERIES SPECIFICATIONS




Cool White
CSRT100RB-CW
CSRT100RW-CW



High Lumen Cool White
CSRT100RB-CWHL
CSRT100RW-CWHL



Warm White
CSRT100RB-WW
CSRT100RW-WW



High Lumen Warm White
CSRT100RB-WWHL
CSRT100RW-WWHL

PERFORMANCE

	Cool White	Warm White	High Lumen Cool White	High Lumen Warm White
CCT	5000K	2700K	5000K	2700K
W/ft	1.46	1.46	2.97	2.97
lm/ft	146	132	289	259
Cut Length	4"	4"	2"	2"
Max Run Length*	50'	50'	35'	35'

*See FAQ page 19 for more information.

CONTRACTOR SERIES CONNECTORS

Bridge gaps & obstacles between 24V LED Ribbon Tape

INTERCONNECTORS	
CSRT2IC	2" Connector Cable
CSRT6IC	6" Connector Cable
CSRT12IC	12" Connector Cable
CSRT24IC	24" Connector Cable
CSRT4FTIC	4' Connector Cable
CSRT8FTIC	8' Connector Cable
CSRTBIC	Butt End Connector

CONTRACTOR SERIES DRIVERS

24V Drivers

CSRTDRIVER75HC
24V 75W non-dimmable driver for indoor use

CSRT60DWT
24V 60W dimmable low voltage transformer

CSRTDRIVER108HC
24V 108W non-dimmable driver for indoor use

CSRT96DWT
24V 96W dimmable low voltage transformer