



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

DESCRIPTION

SLNLEDT Series



The SLNLEDT narrow strip series is suitable for general purpose lighting in a wide variety of environments. The LEDT Series offered by Tamlite are designed and UL listed to work with LED tubes. The LEDT Series is designed to reduce contractor installation time by adding the tubes at the factory while still keeping the UL Listing of the fixture.



FEATURES & SPECIFICATIONS

Input Voltage
120-277 VAC

Frequency
50/60Hz

Operating Temp
-20°C ~ 45°C (-4°F ~ 113°F)

Storage Temp
-40°C ~ 85°C (-40°F ~ 185°F)

CRI
82

Lamp Shape
Linear

Power Factor
0.9

Lamp Style
Linear T8

Socket Type
G13 Bi-pin

Construction

The body is constructed of 24 gauge, made in USA commercial grade steel with hot dip galvanized finish (6.5µm on both sides). Finish: Paint after fabrication (PAF) of galvanized body adds high resistance to rust over its lifetime.

Mounting

Continuous row mounting capability using a chase nipple. Numerous knockouts for easy installation. This fixture may be suspended via optional cable hanging kit.

Listing

UL listed to US and Canadian safety standards. Damp location listed. Fixtures are Assembled in America.

Warranty

Guaranteed for five years from the purchase date of the product, against mechanical defects in manufacturing.

Made in the USA


NOTE: Actual performance may differ as a result of end-user environment and application. All values are designed or typical values, measured under laboratory conditions at 20°C. Specifications subject to change without notice



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

LINE DRAWING

DIMENSION	L	W	H
2FT	24"	3.375"	2.5"
4FT	48"	3.375"	2.5"
8FT	96"	3.375"	2.5"



ORDERING INFORMATION

Example: SLNLEDT2-9D1L840

SERIES	LENGTH	LAMP WATTAGE	LAMP QTY	LAMPS INCLUDED	LAMP WIRING	OPTIONS
SLNLEDT	[2] : 2FT [4] : 4FT [8] : 8FT	[Blank] : No Lamps [-9] : 9W Lamp* [-18] : 18W Lamp**	[D1] : 1 Lamp [D2] : 2 Lamps***	[Blank] : No Lamps	[Blank] : Single Ended Wiring [-DE] : Double Ended Wiring	[Blank] : No Options [-EM] : Emergency Backup [-OS] : Occupancy Sensor [-WG] : Wire Guard [W6-3] : Flex Whip-6' 3 Wire**** [WC6-515] : Cord-6' SJ-515 Plug****
				[L] : Lamps Included	CRI & COLOR TEMP [840] : 4000K [850] : 5000K	

*Option only available on 2FT fixture.

**Option only available on 4 FT & 8 FT fixtures.

***Option only available on 8FT fixture.

**** More options available please contact factory.

LAMP SPECIFICATIONS

SERIES	LAMP WATTAGE (PER LAMP)	EFFICACY (PER LAMP)	LAMP OPERATING CURRENT (PER LAMP)	LAMP LUMENS (PER LAMP)	CRI	NUMBER OF LEDS (PER LAMP)
SLNLEDT2	9 Watts	128 lm/W	35-80 mA	1150 lm	82 CRI	44
SLNLEDT4	18 Watts	122 lm/W	65-155 mA	2200 lm	82 CRI	80
SLNLEDT8	18 Watts	122 lm/W	65-155 mA	2200 lm	82 CRI	80

COMPATIBLE FUSION LAMPS



SLNLEDT2
FLED9T8/840/BYPASS • 0308-8620
FLED9T8/850/BYPASS • 0308-8623



SLNLEDT4 & SLNLEDT8
FLED18T8/840/BYPASS • 0308-8614
FLED18T8/850/BYPASS • 0308-8617



APPLICATION AND PERFORMANCE SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

ACCESSORIES

TAMGRIP-10FT-KIT
 ALL IN ONE, 10FT HANGER KIT
 0553-3296



* Accessories sold separately.