



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

## SERIES SPECIFICATIONS



### CXPCL Series

The CXPCL series LED exit sign and emergency lighting combination unit, offers long-life, energy efficiency, and uniform illumination with square, glare-free LED light heads.



## CONSTRUCTION

### Housing

Injection-molded, engineering grade, 5VA flame retardant, high-impact thermoplastic.

### Transfer switch

Internal solid-state transfer switch automatically connects the internal battery to lamp heads.

### Chevrons

Easy snap-out chevron directional indicators.

### Illumination

Ultra bright, long life LED

### Charger

Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

### Listing

UL Listed

### Location Rating

Suitable for damp locations

### Warranty

Guaranteed for five years from the purchase date of the product, against mechanical defects in manufacturing. Batteries are pro-rated for two years.

### Compliance


Meets UL924, cULus, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

## MOUNTING SPECIFICATIONS

Easy snap mounting canopy included for top or end mount.

Universal K/O pattern on back plate for wall mount.

## LINE DRAWINGS



APPLICATION AND PERFORMANCE SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

## ELECTRICAL SPECIFICATIONS

### Battery Type

3.6V Rechargeable Ni-CDMH

### Operating Voltage

120/277

### LED Indicator

Charge rate/power "ON" and push to test switch

### Low Voltage Disconnect

Prevents battery from deep discharge

### Emergency Illumination

Minimum 90 Minutes

### Battery Recharge Time

24 Hours

### Wattage

3.5W

## ORDERING INFORMATION

EXAMPLE: CXPCL3RWEM

SERIES	# OF FACES	LETTER COLOR	HOUSING COLOR	BATTERY
CXPCL	[3] Universal Single and Double Face	[R] : Red [G] : Green	[W] : White	[EM] : Battery Backup Standard