



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: HORLEDT

**DESCRIPTION**

**HORLEDT Series**

The HORLEDT series full LED body high bays are ideal for manufacturing, warehousing, commercial and industrial facility lighting applications. The LEDT Series offered by TamLite Lighting is a series of commercial grade high bay fixtures designed and UL listed to work with LED tubes. They have been converted to allow for 4ft 18 Watt Direct Bypass LED Tubes. The LEDT Series is designed to reduce contractor installation time by adding the tubes at the factory while still keeping the UL Listing of the fixture.



**FEATURES & SPECIFICATIONS**

**Input Voltage**

120-277 VAC

**Frequency**

50/60Hz

**Operating Temp**

-20°C ~ 45°C (-4°F ~ 113°F)

**Storage Temp**

-40°C ~ 85°C (-40°F ~ 185°F)

**CRI**

82

**Lamp Shape**

Linear

**Power Factor**

0.9

**Lamp Style**

Linear T8

**Socket Type**

G13 Bi-pin

**Construction**

The body is constructed of 24 gauge, made in USA commercial grade steel with hot dip galvanized finish (6.5µm on both sides). Finish: Paint after fabrication (PAF) of galvanized body adds high resistance to rust over its lifetime.

**Mounting**

Not intended for continuous row mounting. This fixture may be suspended via optional cable hanging kit or surface mounted.

**Listing**

UL listed to US and Canadian safety standards. Damp location listed. Fixtures are Assembled in America.

**Warranty**

Guaranteed for five years from the purchase date of the product, against mechanical defects in manufacturing.



**Made in the USA**

NOTE: Actual performance may differ as a result of end-user environment and application. All values are designed or typical values, measured under laboratory conditions at 20°C. Specifications subject to change without notice



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: HORLEDT

**LINE DRAWING**



**ORDERING INFORMATION**

Example: HORLEDT44-18D5L850

SERIES	LENGTH	WIDTH	WATTAGE	LAMP QTY	LAMPS INCLUDED	LAMP WIRING	OPTIONS
HORLEDT	[ 4 ] : 4'	[ 4 ] : 13.75"	[ -18 ] : 18W	[ D4 ] : 4 Lamps [ D6 ] : 6 Lamps [ D9 ] : 9 Lamps	[ BLANK ] : No Lamps	[ -BLANK ] : Single Ended Wiring [ -DE ] : Double Ended Wiring	[ M ] : Mirror Reflector [ -EM ] : Emergency Backup [ -OS ] : Occupancy Sensor [ -WG ] : Wire Guard [ W6-3 ] : Flex Whip-6' 3 Wire* [ WC6-515 ] : Cord-6' SJ-515 Plug* [ HT ] : High Bay Hanger
		[ 6 ] : 19.875"		[ D13 ] : 13 Lamps	[ L ] : Lamps Included	<b>CRI &amp; COLOR TEMP</b> [ 840 ] : 4000K [ 850 ] : 5000K	

**LAMP SPECIFICATIONS**

SERIES	LAMP WATTAGE (PER LAMP)	EFFICACY (PER LAMP)	LAMP OPERATING CURRENT (PER LAMP)	LAMP LUMENS (PER LAMP)	CRI	NUMBER OF LEDS (PER LAMP)
HORLEDT	18 Watts	122 lm/W	65-155 mA	2200 lm	82 CRI	80

APPLICATION AND PERFORMANCE SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	

**LED TUBES SOLD SEPARATELY**



**HORLEDT**  
FLED18T8/840/BYPASS • 0308-8614  
FLED18T8/850/BYPASS • 0308-8617



**ACCESSORIES**

**TAMGRIP-10FT-KIT**  
ALL IN ONE, 10FT HANGER KIT  
0553-3296



\* Accessories sold separately.