

MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

The TAVL combines modern technology with a simple and elegant design. By using LED as a light source, the TAVL fixtures are long lasting and energy efficient. Fixtures are suitable for wall mounting.



DIMENSIONS

24" Length : 24.625", Depth : 3.5", Height : 2.125"

36" Length : 36.0", Depth : 3.0", Height : 4.25"

CONSTRUCTION

Housing
Steel

Finish
Satin Nickel

Lens Material
High transmission acrylic

Diffuser Finish
Frosted

ELECTRICAL SPECIFICATIONS

Input Voltage
120-277 VAC

Input Wattage @ 120V
24" : 17.68W
36" : 23W

Efficacy
24" : 72+ lm/W
36" : 92 lm/W

CRI
>93

Color Temp
3000K

Power Factor
> .9

THD
< 20%

Number of LEDs
24" : 40
36" : 60

L70 Lifespan
<54000 Hours

Operating Temp.
-25°C ~ +75°C

Ambient Temperature
-20°C ~ + 40°C

Beam Angle 24"
[C0/180] Total=108.3,
[C90/270] Total=196

Lumens
24" : 1250+
36" : 2100+

Beam Angle 36"
[C0/180] Total=108.3,
[C90/270] Total=201.2

MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
ETL Listed

Location Rating
Suitable for damp locations

Warranty

Guaranteed for three years from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Sample Part Number: TAVL24-3SN

TAVL			SN
SERIES	LENGTH	COLOR TEMP	FINISH
TAVL	[24] : 24"	[-3] : 3000K	[SN] : Satin Nickel
	[36] : 36"	[-4] : 4000K	