



# TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986  
tel: (772) 878-4944 or on the web at [www.tamliteusa.com](http://www.tamliteusa.com)

## SPECIFICATION & FEATURES

### DESCRIPTION

Lay-Ins' high bay fixtures are designed to meet your industrial lighting requirements, featuring 4, 6, 8, and 10 lamp options in both T5 and T8 configurations. Complete with an aluminum high reflectance polished reflector, the Lay-Ins high bay fixture offers maximum performance to serve today's industrial requirements with the benefit of energy savings.

### HOUSING

Hot dipped galvanized uni-body construction with inter-locking design  
Painted After Fabrication (PAF)- safe handling and added corrosion resistance  
Venting- keeps operating temperatures low, prolonging the life of the fixture  
Hinged reflector- allows access to electrical components without lamp removal  
Four corner suspension openings- standard for chain or aircraft cable mounting

### ELECTRICAL DETAILS

#### T8 BALLAST INFORMATION:

Standard ballast is electronic instant start, thermally protected, resetting, Class P, non-PCB, UL listed, and sound rated A.

#### T5 BALLAST INFORMATION:

Standard ballast is electronic program start, thermally protected, resetting, Class P, non-PCB, UL listed, and sound rated A.

NEC required ballast disconnect pre-installed

### LISTINGS/RATINGS/COMPLIANCE

Fixtures are UL listed and suitable for damp locations.

### WARRANTY

Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

### NOTES

Product performance may vary depending on model and end user environment.

\*\*\* SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE\*\*\*

|              |            |
|--------------|------------|
| Catalog #:   | 05/16/2017 |
| Project:     | Type:      |
| Prepared By: |            |

## HOR Series

### Full Body Fluorescent High Bay



### SPECIFICATIONS / DIMENSIONS



| DIMENSIONS | L       | W       | H      |
|------------|---------|---------|--------|
| 4 LAMP     | 48 3/8" | 13 3/4" | 3 3/4" |
| 6 LAMP     | 48 3/8" | 19 7/8" | 3 3/4" |
| 8 LAMP     | 48 3/8" | 26"     | 3 3/4" |
| 10 LAMP    | 48 3/8" | 32 1/8" | 3 3/4" |

### ORDERING INFORMATION

Sample Part Code: HORT5654MVL

| HOR    |                                              |                                                            |                                                                     |                                                                                                                                                                                                                                                                                                                          |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                         |                                 |                                           |
|--------|----------------------------------------------|------------------------------------------------------------|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|-------------------------------------------|
| SERIES | LAMP TYPE                                    | LAMP QTY                                                   | LAMP WATTAGE                                                        | VOLTAGE                                                                                                                                                                                                                                                                                                                  | LAMPS INCLUDED                                                                                                    | OPTION                                                                                                                                                                                                                                                                                                                                                                                                                  | REFLECTOR                       | COLOR                                     |
| HOR    | [T5]: T5 Fluorescent<br>[T8]: T8 Fluorescent | [4]: 4 Lamp<br>[6]: 6 Lamp<br>[8]: 8 Lamp<br>[10]: 10 Lamp | [25]: 25W T8<br>[28]: 28W T5 & T8<br>[32]: 32W T8<br>[54]: 54W T5HO | [MV]: 120-277V (1 ballast)<br>[MV2]: 120-277V (switching ballast)<br>[Z]: 480V<br>[MVPRS]: 120-277V T8 Program Rapid Start<br>[MVS DIM]: 120-277V Step Dimming*<br>[MVD1MK7]: 120-277V 0-10V Elec. Dimming*<br>[AMK10]: 120V Line Voltage Dimming*<br>[BMK10]: 277V Line Voltage Dimming*<br>*Controller Sold Separately | [BLANK]: No Lamps<br>[L]: (Standard 841K)<br>[L835]: CRI±80 3500K<br>[L841]: CRI±80 4100K<br>[L850]: CRI±80 5000K | [BLANK]: No Options<br>[W1]: 6ft Flex (1 cir.)<br>[W3]: 10ft Flex (1 cir.)<br>[W4]: 10ft Flex (2 cir.)<br>[B2]: 1400 Lumen Single Lamp Emergency Ballast*<br>[F]: Fused<br>[OS]: Occupancy Sensor Cord<br>[HT]: Triangle Hangers (4/6 Only)<br>[-CEE]: CEE Approved Ballast<br>[B2W2]: Emergency 1 Imp 1400 lumens/6ft Whip 2 Cir.<br>[PD]: Pendant Mount Body<br>[LC1]: S80 Clear Smooth Acrylic .095 thick (standard) | [BLANK]: Specular<br>[W]: White | [BLANK]: Std. White<br>[B]: Stealth Black |