



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

DESCRIPTION



W1LED SERIES

Wattage/Color Selectable LED Wall Pack

The W1LED wall pack with its traditional body style is an ideal replacement for HID wall packs. Advantages include long life, instant on/off and lower energy consumption.



FEATURES AND SPECIFICATIONS

Intended Use

The W1LED wall pack is ideal for lighting small areas or walkways. This wall pack is especially useful for security lighting in residential or small to medium commercial buildings.

Construction

Die cast aluminum housing with removable hinged door with gasket and captive corrosion resistant stainless steel screws. 1/2" coin plugs with O-rings for conduit entry on both sides and top.

Finish

Powder coat

Optics

Molded wedge shaped prismatic surface borosilicate glass lens provides a beam angle of 120°.

Electrical

Long-life LEDs, coupled with high-efficiency drivers, provide extended service life. The W1LED delivers up to 129 lumens per watt. Thermally protected driver standard.

Dimming

Step dimming via wattage selection switch

Installation

Fixture has cast-in template for mounting directly over a 4" recessed box or 1/2" coin plugs with O-rings for surface mount conduit connection.

Listings

UL listed to US and Canadian safety standards. Wet location listed. For use in ambient operating temperatures ranging from -40°~+40°C. DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.


Photocell

Integrated photocell with ON/OFF switch.

Warranty

5-year limited warranty.

LINE DRAWING





CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

ORDERING INFORMATION

EXAMPLE: W1LED-WS-3CS

SERIES	WATTAGE	COLOR TEMP	HOUSING COLOR
W1LED	[-WS] : Selectable 10W/20W/30W	[-3CS] : Selectable 3000K/4000K/5000K	[BLANK] : Bronze

PERFORMANCE SPECIFICATIONS


GENERAL DRIVER INFORMATION

ELECTRICAL SPECIFICATIONS		
Input		
Input Voltage (VAC)	120V-277V (+/- 10%)	
Frequency Range (Hz)	50-60 Hz (+/- 10%)	
	120V	277V
Input Current Max (A) Per Driver	1	0.36
THD @ Full Load	<15%	<20%
Efficiency @ Full Load	92%	>89%
Power Factor @ Full Load	>0.9	
Output		
Dimming	0-10V	

LUMEN BREAKDOWN

WATTAGE	LUMENS
10w	1800lm
20w	3200lm
30w	4200lm

PHOTOCELL SWITCH






CONTRACTOR:		DATE:	
PROJECT:		MODEL#:	
PREPARED BY:			


PHOTOMETRIC REPORTS

WILED-WS-5K @10W


Luminous Intensity Distribution Curve



Illuminance at a Distance



IsoLux Plot



APPLICATION AND PERFORMANCE SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION




CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:


PHOTOMETRIC REPORTS

WILED-WS-5K @30W


Luminous Intensity Distribution Curve



Illuminance at a Distance



IsoLux Plot



APPLICATION AND PERFORMANCE SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION