



| | |
|--------------|-------|
| PROJECT: | |
| LOCATION: | |
| MODEL#: | TYPE: |
| CLIENT: | QTY: |
| PREPARED BY: | DATE: |

TATFLL5030BZ

SERIES SPECIFICATIONS

The TATFLL floodlight is a versatile unit with multiple mounting options that satisfies many lighting applications. The TATFLL can be adjusted to almost any position to direct light where needed.



LUMINAIRE SPECIFICATIONS

Beam Angle: 120°
Luminaire Type: Flood Light

LAMP SPECIFICATIONS

Average Life: 50,000hr
Lamp Type: LED

Mean Lumen Output: 3600lm

LIGHT SOURCE SPECIFICATIONS

CRI: 80
Nominal CCT: 5000K

ELECTRICAL SPECIFICATIONS

Ballast Type: LED Driver
Rated Input Voltage: 120VAC / 277VAC

Wattage: 30W

CERTIFICATIONS

Code Compliance: UL

ENVIRONMENTAL SPECIFICATIONS

IP Rating: IP65
UL Location Rating: Wet Location



| | |
|--------------|-------|
| PROJECT: | |
| LOCATION: | |
| MODEL#: | TYPE: |
| CLIENT: | QTY: |
| PREPARED BY: | DATE: |

PHYSICAL SPECIFICATIONS

Finish Color: Bronze
Finish Type: Powder Coated
Housing Material: Aluminum
Lens Material: Polycarbonate

Mounting: Yoke Mount
Weight: 1.3lbs

WARRANTY INFORMATION

Warranty: 5 Years

SHIPPING SPECIFICATIONS

Case

QTY: 1
Weight: 1.25lbs

Master Case

Height: 15 in. **Weight:** 5.25lbs
Length: 20.5 in. **Width:** 11.5 in.
QTY: 4