



PROJECT:	
LOCATION:	
MODEL#:	TYPE:
CLIENT:	QTY:
PREPARED BY:	DATE:

TATFLL5030BZK

SERIES SPECIFICATIONS

The TATFLL floodlight is a versatile unit with multiple mounting options that satisfies many lighting applications. The TATFLL can be adjusted to almost any position to direct light where needed.



LUMINAIRE SPECIFICATIONS

Luminaire Type: Flood Light

LAMP SPECIFICATIONS

Average Life: 50,000hr
Lamp Type: LED

Mean Lumen Output: 3600lm

LIGHT SOURCE SPECIFICATIONS

CRI: 80
Nominal CCT: 5000K

ELECTRICAL SPECIFICATIONS

Ballast Type: LED Driver
Rated Input Voltage: 120VAC / 277VAC

Wattage: 30W

CERTIFICATIONS

Code Compliance: UL

ENVIRONMENTAL SPECIFICATIONS

IP Rating: IP65
UL Location Rating: Wet Location



PROJECT:	
LOCATION:	
MODEL#:	TYPE:
CLIENT:	QTY:
PREPARED BY:	DATE:

PHYSICAL SPECIFICATIONS

Finish Color: Bronze
Finish Type: Powder Coated
Housing Material: Aluminum
Lens Material: Polycarbonate

Mounting: Knuckle Mount
Weight: 1.2lbs

WARRANTY INFORMATION

Warranty: 5 Years

SHIPPING SPECIFICATIONS

Case

QTY: 1
Weight: 1.25lbs

Master Case

Height: 11 in. **Weight:** 12lbs
Length: 19.75 in. **Width:** 15 in.
QTY: 10