



PROJECT:	
LOCATION:	
MODEL#:	TYPE:
CLIENT:	QTY:
PREPARED BY:	DATE:

## TATFLL5015WHK

### SERIES SPECIFICATIONS

The TATFLL floodlight is a versatile unit with multiple mounting options that satisfies many lighting applications. The TATFLL can be adjusted to almost any position to direct light where needed.



### LUMINAIRE SPECIFICATIONS

**Beam Angle:** 120°  
**Luminaire Type:** Flood Light

### LAMP SPECIFICATIONS

**Average Life:** 50,000hr  
**Lamp Type:** LED

**Mean Lumen Output:** 1700lm

### LIGHT SOURCE SPECIFICATIONS

**CRI:** 80  
**Nominal CCT:** 5000K

### ELECTRICAL SPECIFICATIONS

**Ballast Type:** LED Driver  
**Rated Input Voltage:** 120VAC / 277VAC

**Wattage:** 15W

### CERTIFICATIONS

**Code Compliance:** UL

### ENVIRONMENTAL SPECIFICATIONS

**UL Location Rating:** Wet Location



PROJECT:	
LOCATION:	
MODEL#:	TYPE:
CLIENT:	QTY:
PREPARED BY:	DATE:

## PHYSICAL SPECIFICATIONS

**Finish Color:** White  
**Finish Type:** Powder Coated  
**Housing Material:** Aluminum  
**Lens Material:** Polycarbonate

**Mounting:** Knuckle Mount  
**Weight:** 0.43lbs

## WARRANTY INFORMATION

**Warranty:** 5 Years

## SHIPPING SPECIFICATIONS

### Case

**QTY:** 1  
**Weight:** 0.5lbs

### Master Case

**Height:** 7 in.                      **Weight:** 7.75lbs  
**Length:** 17.5 in.                **Width:** 13.5 in.  
**QTY:** 18