



PROJECT:	
LOCATION:	
MODEL#:	TYPE:
CLIENT:	QTY:
PREPARED BY:	DATE:

## TATFLL5050WHK

### SERIES SPECIFICATIONS

The TATFLL floodlight is a versatile unit with multiple mounting options that satisfies many lighting applications. The TATFLL can be adjusted to almost any position to direct light where needed.



<b>IP65</b> RATING	<b>120V</b> OPERATING VOLTAGE	<b>277V</b> OPERATING VOLTAGE	<b>5 YEAR</b> LIMITED WARRANTY
-----------------------	-------------------------------------	-------------------------------------	--------------------------------------

### LUMINAIRE SPECIFICATIONS

Beam Angle: 120°  
Luminaire Type: Flood Light

### LAMP SPECIFICATIONS

Average Life: 50,000hr  
Lamp Type: LED

Mean Lumen Output: 6000lm

### LIGHT SOURCE SPECIFICATIONS

CRI: 80  
Nominal CCT: 5000K

### ELECTRICAL SPECIFICATIONS

Ballast Type: LED Driver  
Rated Input Voltage: 120VAC / 277VAC

Wattage: 50W

### CERTIFICATIONS

Code Compliance: UL

### ENVIRONMENTAL SPECIFICATIONS

IP Rating: IP65  
UL Location Rating: Wet Location



PROJECT:	
LOCATION:	
MODEL#:	TYPE:
CLIENT:	QTY:
PREPARED BY:	DATE:

## PHYSICAL SPECIFICATIONS

**Finish Color:** White  
**Finish Type:** Powder Coated  
**Housing Material:** Aluminum  
**Lens Material:** Polycarbonate

**Mounting:** Knuckle Mount  
**Weight:** 1.7lbs

## WARRANTY INFORMATION

**Warranty:** 5 Years

## SHIPPING SPECIFICATIONS

**Case**

**QTY:** 1  
**Weight:** 1.75lbs

**Master Case**

**Height:** 11 in.                      **Weight:** 10.25lbs  
**Length:** 14.5 in.                 **Width:** 9.5 in.  
**QTY:** 6