



PROJECT:	
LOCATION:	
MODEL#:	TYPE:
CLIENT:	QTY:
PREPARED BY:	DATE:

W2LED-WS-3CS

SERIES SPECIFICATIONS

Experience enhanced outdoor lighting with the W2LED series wall pack, perfect for commercial properties and security enhancements. The housing size makes the W2LED a direct upgrade for most common HID wall packs. Featuring wattage and color selectable technology along with an integrated photocell, it allows easy on-site customization to meet a wide range of lighting requirements.



LUMINAIRE SPECIFICATIONS

Efficacy: 138lm/W
Lumen Output: 6900/8300/11050lm
Luminaire Beam Angle: 120°

Luminaire Type: Wall Pack

LIGHT SOURCE SPECIFICATIONS

CRI: 80
Nominal CCT: 3000K/4000K/5000K

Source Type: LED

ELECTRICAL SPECIFICATIONS

Ballast Type: LED Driver
Dimming: 0-10V
Input Frequency: 50Hz / 60Hz

Rated Input Voltage Range: 120-277VAC
Wattage: 80/60/50W

SENSOR SPECIFICATIONS

Sensor Type: Photocell

CERTIFICATIONS

Performance Certifications: DLC
Safety Certifications: UL Listed

ENVIRONMENTAL SPECIFICATIONS

IP Rating: IP65
Temperature Rating Range: -40-40°C

UL Location Rating: Wet Location



PROJECT:	
LOCATION:	
MODEL#:	TYPE:
CLIENT:	QTY:
PREPARED BY:	DATE:

PHYSICAL SPECIFICATIONS

Finish Color: Bronze
Finish Type: Powder Coat
Housing Material: Aluminum
Lens Material: Tempered Glass

Mounting: Surface Mount
Weight: 13.5lbs
Wiring Type: 3-Wire (L-N-G) 2-wire(010Vdc)

WARRANTY INFORMATION

Warranty: 5 Years

SHIPPING SPECIFICATIONS

Package

QTY: 1

Master Case

Height: 11.625 in.
Length: 15.375 in.
QTY: 1

Weight: 9.5lbs
Width: 9 in.